SHEETS CHANDELIER





SHEETS CHANDELIER

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect the item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

BEFORE YOU BEGIN


- Have the chandelier installed by a qualified electrician, following local electrician codes.
- Switch off power at the breaker before starting, and use a voltage tester to confirm there is no live current.
- Make sure the ceiling steructure or junction box can support at least twice the chandelier's total weight.
- Check the LED driver for dimmer compatibility before installation


1. Test the fixture

- Switch off the circuit breaker and confirm power is off with a voltage tester.

2. Prepare the Ceiling & Junction Box

- Inspect the junction box or structural mounting points for strength.
- Add blocking if needed.
- Mark canopy center and plan pendant drop lengths.






3. Remove Mounting Bracket

- Inspect the junction box or structural mounting points for strength.
- Add blocking if needed.
- Mark canopy center and plan pendant drop lengths.

4. Attach Diffusers

- Put on gloves.
- Align diffusers with LED base rods and secure with provided screws.
- Tighten evenly using the correct tool.







5. Install Mounting Bracket

- Place bracket against the ceiling.
- Secure the machine screws into junction box or lag screws into blocking.
- Make sure the bracket is level.

6. Wire the Fixture

- Connect hot (black/brown) to hot, neutral (white/blue) to neutral, and ground (green/yellow) to building ground.
- For remote drivers, run low voltage cables as shown in CAD diagrams, ensuring correct polarity.







7. Secure the Canopy


- Lift the canopy over the bracket.
- Attach with decorative screws or caps, tightening all sides evenly.
- Check all strain reliefs are gripping cables properly.

8. Remove Protective Film

- Peel away any protective plastic from the canopy and diffusers.







9. Adjust Pendant Lights

- Press cable gripper tabs to raise or lower pendants.
- Check alignment and spacing.
- Trim extra cable above grippers, leaving a small loop for adjustments.

10. Final Test

- Restore power.
- Test at full brightness.



WARRANTY INFORMATION

Damages or Issues:

- Start a return/exchange online and mark the item as damaged
- After 30 days, coverage applies only with an extended warranty
- Submit photos/videos we'll assess and offer a replacement

Standard Warranty

All fixtures are covered for manufacturer defects for 30 days. Contact us with proof for a free replacement.

Extended Warranty

Available for 12, 36, or 60 months. Includes:

- Free instant replacements
- Accident & manufacturer protection
- Component coverage (excludes bulbs)

Contacts



Shop Online at www.residencesupply.com



Follow our Instagram @residencesupply



24/7 Customer Service +1 (800)-791-7436